

**In the Claims:**

Please amend claims 1-5 as indicated below.

1. (Currently amended) A computer-implemented method, comprising:

in response to a metadata server receiving a data access request from a client, [[a]]  
the metadata server:

determining a maximum expiration time indicated by a next scheduled  
quiesce time;

wherein the data access request is for data that is also accessible by one or  
more other clients each having a corresponding unexpired token,  
and wherein said quiesce time is a time when exclusive access to  
the data is required by a task;

generating an access token that grants the client access to data stored on  
one or more storage devices associated with the metadata server,  
wherein the access token comprises an expiration time; and

wherein said generating an access token comprises setting the expiration  
time of the access token to be no later than the maximum  
expiration time indicated by the next scheduled quiesce time.

2. (Currently amended) The computer-implemented method of claim 1, further  
comprising:

determining a default expiration time; and

if the default expiration time is earlier than the maximum expiration time, setting the expiration time of the access token to be the default expiration time.

3. (Currently amended) The computer-implemented method of claim 1, further comprising the metadata server providing the access token to the client.

4. (Currently amended) The computer-implemented method of claim 3, further comprising:

a storage device receiving a data I/O request associated with the access token;

comparing a current system time with the access token's expiration time;

denying the data I/O request if the current system time is later than the access token's expiration time.

5. (Currently amended) The computer-implemented method of claim 4, wherein:

the client is one of a plurality of clients;

the access token is one of a plurality of access tokens;

each of the access tokens is provided to a respective one of the plurality of clients;

and

wherein at the next scheduled quiesce time the plurality of access tokens are expired without the metadata server transmitting a message to each client to expire its respective access tokens.

6. (Previously presented) A system, comprising:

a metadata server, wherein the metadata server is configured to:

determine a maximum expiration time indicated by a next scheduled quiesce time in response to receiving a data access request from a client;

wherein the data access request is for data that is also accessible by one or more other clients each having a corresponding unexpired token, and wherein said quiesce time is a time when exclusive access to the data is required by a task;

generate an access token that grants the client access to data stored on one or more storage devices associated with the metadata server, wherein the access token comprises an expiration time; and

set the expiration time of the access token to be no later than the maximum expiration time.

7. (Original) The system of claim 6, wherein the metadata server is further configured to:

determine a default expiration time; and

set the expiration time of the access token to be the default expiration time if the default expiration time is earlier than the maximum expiration time.

8. (Original) The system of claim 6, further comprising a storage device, wherein the storage device is configured to:

receive a data I/O request associated with the access token;

compare a current system time with the access token's expiration time; and

deny the data I/O request if the current system time is later than the access token's expiration time.

9. (Previously presented) The system of claim 8, wherein the metadata server is further configured to:

provide the access token to the client.

10. (Original) The system of claim 9, wherein:

the access token is one of a plurality of access tokens; and

wherein the metadata server is further configured to:

provide one access token of the plurality of access tokens to a respective one of a plurality of clients; and

wherein at the next scheduled quiesce time the plurality of access tokens are expired without the metadata server transmitting a message to each client to expire its respective access tokens.

11. (Previously presented) A computer-readable, storage medium, comprising program instructions configured to implement:

a metadata server determining a maximum expiration time indicated by a next scheduled quiesce time;

generating an access token that grants a client access to data stored on one or more storage devices associated with the metadata server, wherein the

access token comprises an expiration time, wherein the data is also accessible by one or more other clients each having a corresponding unexpired token, and wherein said quiesce time is a time when exclusive access to the data is required by a task; and

setting the expiration time of the access token to be no later than the maximum expiration time.

12. (Previously presented) The computer-readable, storage accessible medium of claim 11, wherein the program instructions are further configured to implement:

determining a default expiration time; and

if the default expiration time is earlier than the maximum expiration time, setting the expiration time of the access token to be the default expiration time.

13. (Previously presented) The computer-readable, storage accessible medium of claim 11, wherein the program instructions are further configured to implement:

receiving a data I/O request associated with the access token;

comparing a current system time with the access token's expiration time; and

denying the data I/O request if the current system time is later than the access token's expiration time.

14. (Previously presented) The computer-readable, storage accessible medium of claim 13, wherein the program instructions are further configured to implement:

receiving a data access request from the client; and

providing the access token to the client.

15. (Previously presented) The computer-readable, storage medium of claim 14, wherein:

the client is one of a plurality of clients;

the access token is one of a plurality of access tokens;

each of the access tokens is provided to a respective one of the plurality of clients;  
and

wherein at the next scheduled quiesce time the plurality of access tokens are expired without the metadata server transmitting a message to each client to expire its respective access tokens.

16. (Previously presented) A system, comprising:

means for determining a default expiration time;

means for setting the expiration time of an access token to the earlier of either a maximum expiration time indicated by a next scheduled quiesce time or the default expiration time, wherein the access token grants a client access to data stored on one or more storage devices associated with a metadata server;

means for receiving a data I/O request associated with the access token, wherein the data I/O request is for data that is also accessible by one or more other clients each having a corresponding unexpired token, and wherein said quiesce time is a time when exclusive access to the data is required by a task;

means for comparing a current system time with the access token's expiration time; and

means for denying the data I/O request if the current system time is later than the access token's expiration time.